

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST
CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product
Produit

Multiple Portable Socket Outlets

Name and address of the applicant
Nom et adresse du demandeur

ALING-CONEL d.o.o.
Železnička 10, 21432 Gajdobra, Serbia

Name and address of the manufacturer
Nom et adresse du fabricant

ALING-CONEL d.o.o.
Železnička 10, 21432 Gajdobra, Serbia

Name and address of the factory
Nom et adresse de l'usine

ALING-CONEL d.o.o.
Železnička 10, 21432 Gajdobra, Serbia

Note: When more than one factory, please report on page 2
Note: Lorsque il y a plus d'une usine, veuillez utiliser la 2^{ème} page

☐ Additional Information on page 2

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

See Page 2

Trademark (if any)
Marque de fabrique (si elle existe)

ALING-CONEL

Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur

/

Model / Type Ref.
Ref. De type

art.4431x; art.4433x; art.4435x; art.4436x; art.44301x;
art.44303x; art.44305x; art.44306x; art.4451x; art.4453x;
art.4455x; art.4456x; art.44501x; art.44503x; art.44505x;
art.44506x; art.4461x; art.44601x; art.44701x; art.44801x

Additional information (if necessary may also be reported
on page 2)
Les informations complémentaires (si nécessaire, peuvent
être indiqués sur la 2^{ème} page

☒ Additional Information on page 2

A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a été
considéré conforme à la

IEC 60884-1:2002 (3rd Ed.) + A1:2006

As shown in the Test Report Ref. No. which forms part of
this Certificate
Comme indiqué dans le Rapport d'essais numéro de
référence qui constitue partie de ce Certificat

T211-0425/13


This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**



Slovenski institut za kakovost in meroslovje
Slovenian Institute of Quality and Metrology
Tržaška c. 2, SI-1000 Ljubljana, Slovenia
Product Certification Body is accredited by Slovenian Accreditation, Reg. No.: CP-001

Date: 2013-08-08

Signature: Alja Pregl



General product information:

1. Multiple portable socket outlets (3 socket-outlets): art.4431x; art.4433x; art.4435x; art.4436x;

(last number denotes cable length (1=1,5 m, 3=3 m, 5=5 m, 6=10 m);

x denotes color of enclosure (0 (white) or A (anthracite));

Rating: 250 V ~, 16 A

2. Multiple portable socket outlets (3 socket-outlets) with incorporated double-pole switch with indication: art.44301x; art.44303x; art.44305x; art.44306x;

(last number denotes cable length (1=1,5 m, 3=3 m, 5=5 m, 6=10 m);

x denotes color of enclosure (0 (white) or A (anthracite));

Rating: 250 V ~, 16 A

3. Multiple portable socket outlets (5 socket-outlets): art.4451x; art.4453x; art.4455x; art.4456x;

(last number denotes cable length (1=1,5 m, 3=3 m, 5=5 m, 6=10 m);

x denotes color of enclosure (0 (white) or A (anthracite));

Rating: 250 V ~, 16 A

4. Multiple portable socket outlets (5 socket-outlets) with incorporated double-pole switch with indication: art.44501x; art.44503x; art.44505x; art.44506x;

(last number denotes cable length (1=1,5 m, 3=3 m, 5=5 m, 6=10 m)

x denotes color of enclosure (0 (white) or A (anthracite))

Rating: 250 V ~, 16 A

5. Multiple portable socket outlets (5 socket-outlets) with incorporated surge protective device: art.4461x;

(x denotes color of enclosure (0 (white) or A (anthracite))). Cable length 1,5 m.

Rating: 250 V ~, max. load 10 A

6. . Multiple portable socket outlets (5 socket-outlets) with incorporated surge protective device and double-pole switch: art.44601x;

(x denotes color of enclosure (0 (white) or A (anthracite))). Cable length 1,5 m.

Rating: 250 V ~, max. load 10 A

7. Multiple portable socket outlets (5 socket-outlets) with incorporated surge protective device, network filter and double-pole switch: art.44701x;

(x denotes color of enclosure (0 (white) or A (anthracite))). Cable length 1,5 m.

Rating: 250 V ~, max. load 10 A

8. Multiple portable socket outlets (5 socket-outlets) with incorporated surge protective device for mains and telephone connection, network filter and double-pole switch: art.44801x;

(x denotes color of enclosure (0 (white) or A (anthracite))). Cable length 1,5 m.

Rating: 250 V ~, max. load 10 A

Additional information (if necessary)**Information complémentaire (si nécessaire)**

Date: 2013-08-08

Signature: Alja Pregl

